

CERTIFICATE OF ACCREDITATION

This is to certify that

THE METROLOGY UNIT OF THE MAURITIUS STANDARDS BUREAU (MSB)

Calibration Laboratory No. C002

is accredited by the *Mauritius Accreditation Service (MAURITAS)* for the following Calibration fields:

MASS DIMENSIONAL CALIBRATION & TEMPERATURE

as per scope of schedule of accreditation

THIS LABORATORY MEETS THE REQUIREMENTS OF ISO/IEC 17025:2017

This accreditation demonstrates technical competency for a defined scope and the operation of a laboratory quality management system and shall remain in force subject to continuing compliance with MAURITAS accreditation criteria, ISO/IEC 17025:2017 and any further requirements specified by MAURITAS

Issue Date: 31 May 2021 Director of MAURITAS

This certificate is valid only when accompanied by its schedule of Accreditation.



Schedule of Accreditation Laboratory No C002 (accredited to ISO/IEC 17025:2017)

Permanent Address of Laboratory:

Mauritius Standards Bureau Villa Road MOKA

Postal Address:

Mauritius Standards Bureau Villa Road MOKA

Tel No.: (230) 433 3648 **Fax No.:** (230) 433 5051

E-mail: msb@intnet.mu

Technical Signatories:

For Mass and Dimensional Calibration: Miss Vaneeda Radha Ramasawmy

For Temperature:

Mr. Christian Ng Ha Kwong

For Mass Pieces and Non-Automatic

Weighing Instrument: Mr. Tomeswar Pryam

Issue No: 05

Expiry Date: 11 September 2022

	Measured Quantity of Type of Gauge or Instrument	Reference to standardized procedure	Range of Measured Quantity	Calibration and Measurement Capabilities Expressed as an Uncertainty (±)
I.	Mass			
1.	Mass Pieces	MECH-	OIML F ₁ Class	
		MET/LPM-01	1 mg	0.007 mg
		(Mass)	2 mg	0.007 mg
			5 mg	0.007 mg
			10 mg	0.008 mg
			20 mg	0.010 mg
			50 mg	0.013 mg
			100 mg	0.017 mg
			200 mg	0.020 mg
			500 mg	0.027 mg
			1 g	0.03 mg
			2 g	0.04 mg
			5 g	0.05 mg
			10 g	0.07 mg
			20 g	0.08 mg
			50 g	0.10 mg
			100 g to 20 kg	0.000 16 %

The CMC, expressed as an expanded uncertainty of measurement, is stated as the standard uncertainty of measurement multiplied by a coverage factor k = 2, corresponding to a confidence level of approximately 95%

	Measured Quantity of Type of Gauge or Instrument	Reference to standardized procedure	Range of Measured Quantity	Calibration and Measurement Capabilities Expressed as an Uncertainty (±)	
2.	WEIGHING INSTRUMENTS Digital Self Indicating	MECH- MET/LPM-01 (Mass)	1 mg to 50 g 50 g to 2000 g 2 kg to 12 kg 12 kg to 20 kg	0.1 mg 0.000 25 % 0.001 % 0.005 %	
	 Non-Automatic Weighing Instrument 	MECH- MET/LPM-01 (Mass)	20 kg to 100 kg	0.005%	
3.	On-site calibration of items 2				
II.	Dimensional Calibration				
2.	LINEAR DIMENSIONS Line Standards • Engineer Steel Rule VARIOUS DIMENSIONAL Hand Instruments	MECH- MET/LPM-03 (Dimensional)	1 to 1 000 mm	0.10 mm	
	External MicrometerCaliperDial Gauge	MET/LPM-02 (Dimensional)	0 to 125 mm 0 to 300 mm 0 to 30 mm	4.0 μm 10 μm 5.0 μm	
III.	Temperature		0 to 50 mm	υ.υ μπι 	
1.	Thermometers Liquid-in-glass	TEMP- MET/LPM-01 (Temperature)	0.0°C 0°C to 70°C 70°C to 100°C	0.05°C 0.04°C 0.07°C	

The CMC, expressed as an expanded uncertainty of measurement, is stated as the standard uncertainty of measurement multiplied by a coverage factor k = 2, corresponding to a confidence level of approximately 95%

Issued by the Mauritius Accreditation Service (MAURITAS)

Date: 31 May 2021		
•	Director of MAURITAS	